



Unit 1 - 21 Orchard Rd Brookvale NSW Australia 2100 Ph: 61 2 99050383 Email: info@bourkevalves.com.au Web: www.bourkevalves.com.au

## HIGH PRESSURE SAFETY VALVE 15mm (1/2)

High Pressure Safety Relief Valve of the highest quality and performance. Designed and manufactured in accordance with Australian Standards 1271, and suitable for most pressure vessels.

Designation of Bourke Valves part number. Example : HP - 15 - 2000 - BSP



Thread Standard (BSP or NPT) Pressure setting in kPa Thread Size Valve type – HP (High Pressure)

## FEATURES INCLUDE:

- Ring lift manual override.
- Atmospheric discharge.
- Reliable Ball and seat design




## TECHNICAL DATA

BOURKE PART NO.	HP - 15 - #
Size - BSP or NPT	15mm (1/2)
Pressure setting - #	1380-4500 kPa
<b>Temperature Rating(Max.)</b>	220 deg.C
Height - mm	80
Weight - grams	160
Seat	Brass
Body & Cap	Brass
Stem	Brass
Sealing member	Mangenese Bronze
Spring	Stainless Steel
Keyring	Stainless Steel
Seal clip	Zinc Plated Steel

# Specify Pressure Setting required

FLOW RATE CHART



Discharge Capacity Determined at 10% over set pressure

Every valve is factory tested for crack and reseal performance. Specifications are subject to change without notice.

