




Unit 1 - 21 Orchard Rd Brookvale NSW Australia 2100 Ph: 61 2 99050383 Email: info@bourkevalves.com.au Web: www.bourkevalves.com.au

HIGH PRESSURE SAFETY VALVE 25mm (1")

High Pressure Safety Relief Valve of the highest quality and performance. Designed and manufactured in accordance with Australian Standards 1271, and suitable for most pressure vessels.

Designation of Bourke Valves part number.



Thread Standard (BSP or NPT) Pressure setting in kPa Thread Size Valve type – HP (High Pressure)

FEATURES INCLUDE:

- Lever lift manual override.
- Atmospheric discharge.
- Reliable Ball and seat design




TECHNICAL DATA

| BOURKE PART NO. | HP - 25 - # |
|---------------------------------|----------------------------|
| | |
| Size - BSP or NPT | 25mm (1") |
| Pressure setting - # | 1500-4500 kPa (217-650PSI) |
| Temperature Rating(Max.) | 220 deg.C |
| Height - mm | 140 |
| Weight - grams | 1000 |
| Seat | Brass |
| Body & Cap | Brass |
| Stem | Brass |
| Sealing member | Mangenese Bronze-S/Steel |
| Spring | S/Steel, Crome Alloy Steel |
| Lever | Stainless Steel |
| Seal | Stainless Steel |

Specify Pressure Setting required

FLOW RATE CHART



Discharge Capacity Determined at 10% over set pressure

Every valve is factory tested for crack and reseal performance. Specifications are subject to change without notice.

Proudly Australian Made



Australian Owned