




Unit 1-21 Orchard Rd Brookvale NSW Australia 2100 Ph: 61 2 99050383 Email: <u>info@bourkevalves.com.au</u> Web: <u>www.bourkevalves.com.au</u>

## HIGH VOLUME SAFETY VALVE 15mm (1/2)

High Volume Safety Relief Valve of the highest quality and performance. Designed and manufactured in accordance with Australian Standards 1271, and suitable for most pressure vessels.

## Designation of Bourke Valves part number. Example : HV – 15 – 1035 – BSP



Thread Standard (BSP or NPT) Pressure setting in kPa Thread Size Valve type – HV (High Volume)

## FEATURES INCLUDE:

- High discharge capacity.
- Lever lift manual override.
- Atmospheric discharge.
- Reliable Ball and seat design




TECHNICAL DATA	

BOURKE PART NO.	HV - 15 - #
Size - BSP or NPT	15mm (1/2)
Pressure setting - #	242-1725 kPa (35-250 PSI)
Temperature Rating(Max.)	220°C
Height - mm	110
Weight - grams	300
Seat	Brass
Body & Cap	Brass
Stem	Brass
Sealing member	Mangenese Bronze
Spring	Stainless Steel
Lever	Zinc Plated Steel
Seal clip	Zinc Plated Steel

# Specify Pressure Setting required

Proudly Australian Made

FLOW RATE CHART



Discharge Capacity measured at 10% over set pressure

Every valve is factory tested for crack and reseal performance. Specifications are subject to change without notice.



Australian Owned