




Unit 1-21 Orchard Rd Brookvale NSW Australia 2100 Ph: 61 2 99050383 Email: <u>info@bourkevalves.com.au</u> Web: <u>www.bourkevalves.com.au</u>

## RING LIFT SAFETY VALVE 15mm (1/2)

Ring Lift Safety Relief Valve of the highest quality and performance. Designed and manufactured in accordance with Australian Standards 1271, and suitable for most pressure vessels.

Designation of Bourke Valves part number. Example : RL – 15 – 1035 – BSP



Thread Standard (BSP or NPT) Pressure setting in kPa Thread Size Valve type – RL (Ring Lift)

## FEATURES INCLUDE:

- Ring lift manual override.
- Atmospheric discharge.
- Reliable Ball and seat design




## TECHNICAL DATA

| BOURKE PART NO.          | RL - 15 - #             |
|--------------------------|-------------------------|
|                          |                         |
| Size - BSP or NPT        | 15mm (1/2)              |
| Pressure setting - #     | 35-1725 kPa (5-250 PSI) |
| Temperature Rating(Max.) | 220°C                   |
| Height - mm              | 80                      |
| Weight - grams           | 150                     |
| Seat                     | Brass                   |
| Body & Cap               | Brass                   |
| Stem                     | Brass                   |
| Sealing member           | Mangenese Bronze        |
| Spring                   | Stainless Steel         |
| Keyring                  | Stainless Steel         |
| Seal clip                | Zinc Plated Steel       |

# Specify Pressure Setting required

FLOW RATE CHART



Discharge Capacity measured at 10% over set pressure

Every valve is factory tested for crack and reseal performance. Specifications are subject to change without notice.



Proudly Australian Made